

Scotch 35 Vinyl Electrical Tape Green 19 mm x 20 m

Model: Scotch 35

80610833909	Scotch Vinyl Electrical Tape 35 for Color Coding 3/4" X 66' RED 100 rolls per case
80610833925	Scotch Vinyl Electrical Tape 35 for Color Coding 3/4" X 66' BLUE 100 rolls per case
80610833966	Scotch Vinyl Electrical Tape 35 for Color Coding 3/4" X 66' YELLOW 100 rolls per case
80610833982	Scotch Vinyl Electrical Tape 35 for Color Coding 3/4" X 66' WHITE 100 rolls per case
80610834022	Scotch Vinyl Electrical Tape 35 for Color Coding 3/4" X 66' ORANGE 100 rolls per case
80611211576	Scotch Vinyl Electrical Tape 35 for Color Coding 3/4" X 66' GREEN 100 rolls per case

Product Details

- Easy to handle and apply
- Protect electrical conductors, motor leads and piping from abrasion, acids, alkalis, corrosion, moisture and weather
- Remain functional over a wide range of temperatures – up to 105°C
- Feature a pressure sensitive rubber adhesive
- Withstands a temperature range of 32 to 221 °F (0 to 105 °C)
- UL Listed, VDE, CSA Certified and RoHS 2011/65/EU Compliant



Scotch 35 Vinyl Electrical Tape is easy to handle and apply with a pressure sensitive rubber adhesive. This professional grade tape is excellent for phase identification and colour coding of cables or piping systems. It's UL, CSA and VDE approved.

Scotch Tape 35 provides electrical and mechanical protection with the combination of an aggressive, pressure sensitive, rubber resin adhesive and an elastic PVC backing. This tape is flame retardant and is highly resistant to UV rays, abrasion, moisture, alkalis, acids, solvents and varying weather conditions. It stretches easily and adheres virtually in any shape. Ideal for insulating electrical wires and is compatible with synthetic cable insulations, jackets and splicing compounds. UL Listed, VDE, CSA Certified and RoHS 2011/65/EU Compliant.



Specifications

Adhesion to Steel	2,2 N/cm
Adhesive Material	Rubber Resin, The adhesive layer is a rubber-based
Adhesive Type	Rubber
Backing Material	Vinyl
Backing Thickness (metric)	0.18 mm
Brand	Scotch
Chemical Resistant	Yes
Dielectric Strength (V/mil)	1250
Elongation at Break	225%
Flame Retardant	Yes
Insulated	Yes
Insulation Resistance	> 10 ⁶ megohms
Length (Metric)	20 m
Material	PVC
Maximum Operating Temperature (Celsius)	105 Degree Celsius
Operating Temperature (Celsius)	Up to 105 Degree Celsius
Operating Temperature Range (Celsius)	0 °C to 105 °C
Product Type	PVC tape
RoHS 2011/65/EU Compliant	Yes
RoHS EU Comments	RoHS 2011/65/EU compliant without exemption *Important RoHS information
Self-Extinguishing	Yes
Self Sticking/Amalgamating	No
Shelf Life	5 Year
Suitable for High Voltage	No



Tape Colour option	Green, Red, Blue, Yellow, White, Orange
Tape Grade	Professional Use
Tape Type	PVC insulation
Thickness (Metric)	0.178 mm
Total Tape Thickness without Liner (metric)	0.178 mm
UL File Number	E129200
UV Resistant	Yes
Voltage Application	Low Voltage
Voltage Rating	600 V
Vulcanizing	No
Width (Metric)	19.05 mm

